

Limit switch box



- + Visual position indicator
- + Quick-set cam
- + Dual cable entries
- + Captive cover bolts
- + Easy mounting bracket (IS05211)

Weather proof (IP68)	ALS10	Mechanical	2SPDT
	ALS11	Proximity	2SPDT
	ALS12	Mechanical	3SPDT
	ALS13	Mechanical	4SPDT
Explosion proof (Ex d IIC T6)	ALS30	Mechanical	2SPDT
	ALS31	Proximity	2SPDT
	ALS32	Mechanical	3SPDT
	ALS33	Mechanical	4SPDT
	ALS34	Mechanical	2DPDT



Switch Specification		Wiring	
- Safe structure&Long life - Light feeling&Competitive price - UL, CSA, VDE Approved			
Rating	15/16A		
Insulation resistance	Min. 100M		
Dielectric strength	AC 2,000V		
Electrical life	100,000		
GROUND			

Bracket

	Size	Material	Image		Size	Material	Image
ST1	30*80*20 (AR50~ AR160)	Stainless steel		S1	30*80*20~ 30 (AR50~ AR160)	Steel (Powder painted)	
ST3	30*130*30 (AR210~ A300)	Stainless steel		S8	25*25*20 (R32)	Steel (Powder painted)	
				A1	30*80*20 (AR50~ AR160)	Aluminum (Powder painted)	
ST5	25*50*20 (R40)	Stainless steel		A2	30*80(130)*30 (AR210~ A300)	Aluminum (Powder painted)	